

HAULOTTE COMPACT 14 DUAL

ELECTRIC SCISSOR LIFT



TECHNICAL DATA - COMPACT 14 DUAL

Working height - indoor	13.75 m
Working height - outdoor	9.8 m
Platform height - indoor	11.75 m
Platform height - outdoor	7.8 m
Max. drive working height - indoor	11.75 m
Max. drive working height - outdoor	9.8 m
Lift capacity - indoor	320 kg (3 persons)
Lift capacity - outdoor	320 kg (1 person)
Capacity on extension	120 kg
Platform length / extended	2.4 m / 3.32 m
Platform extension	0.92 m
Platform width - outside	1.17 m
Stowed height / rails lowered	2.72 m / 2.02 m
Overall width / length	1.20 m / 2.5 m
Wheelbase	1.86 m
Ground clearance - centre / deployed	12.5 cm / 2 cm
Low drive speed	0.7 / 1.5 / 4.2 km/h
Gradeability	25%
Tilt - longitudinal / lateral	3.5 deg / 1.5 deg
Turning radius - outside	1.83 m
Non-marking tyres	15 x 5
Batteries	24 V - 225 Ah (C20)
Hydraulic system capacity	14 l
Weight	3,070 kg

STANDARD EQUIPMENT

- Indoor and outdoor use
- Foldable guardrails
- Front platform extension
- AC motors
- 27 A multivoltage charger
- Mobile pothole guards
- Swing-out battery access tray
- Forklift pockets
- Motion alarm and flashing light
- Solid non-marking tyres
- Activ Screen diagnostics
- Activ Energy battery management

Source: Haulotte datasheet, February 2026. Product image is illustrative of the Compact range.

**Forklift Truck
Depot Limited**
Buy It | Rent It | Lift It - We've Got the Solution

ACCESS EQUIPMENT HIRE



01226 281673



info@forklifttruckdepot.com